


PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04Q 11/04, 7/00, 3/66, 7/24		A1	(11) International Publication Number: WO 97/04615
			(43) International Publication Date: 6 February 1997 (06.02.97)
(21) International Application Number: PCT/GB96/01711 (22) International Filing Date: 17 July 1996 (17.07.96) (30) Priority Data: 95305116.6 21 July 1995 (21.07.95) EP (34) Countries for which the regional or international application was filed: GB et al. (71) Applicant (for all designated States except US): BRITISH TELECOMMUNICATIONS PUBLIC LIMITED COMPANY [GB/GB]; 81 Newgate Street, London, EC1A 7AJ (GB). (72) Inventors; and (75) Inventors/Applicants (for US only): GOETZ, Ian [GB/GB]; 39 Langdale Road, Thame, Oxfordshire OX9 3WL (GB). GANNON, Stephen, Mark [GB/GB]; 98 Bois Moor Road, Chesham, Buckinghamshire HP5 1SS (GB). MUNDAY, Peter, Robert [GB/GB]; 8 Candleford Close, Bracknell, Berkshire RG12 2JZ (GB). (74) Agent: LIDBETTER, Timothy, Guy, Edwin; BT Group Legal Services, Intellectual Property Dept., Holborn Centre, 8th floor, 120 Holborn, London EC1N 2TE (GB).		(81) Designated States: AL, AM, AT, AU, AZ, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.	

(54) Title: MOBILE TELEPHONE SYSTEM



(57) Abstract

A mobile telephone system consists of a base transceiver station (BTS) that provides radio communication with a mobile handset (MS) and also communicates with a control station (BSC) through a communication link in the form of a leased line which provides a first communication path (P1) with a predetermined bandwidth for signals communicated between the BTS and the BSC. A communication network in the form of an ISDN is used to provide a selectively connectable second communication path (P2) between the BTS and the BSC so as to augment the bandwidth available for the signals during periods of peak demand. In order to accommodate different call connection times in the system through the leased line and the ISDN, the BSC/BTS are arranged to produce call connection signals (CL11, CL12) that initiate billing at the same time irrespective of the path P1, P2 used to make the call connection.

BEST AVAILABLE COPY

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

MOBILE TELEPHONE SYSTEM

This invention relates to a mobile telephone system and a method of providing a communication channel for mobile telephony, and has particular but not
5 exclusive application to digital mobile systems, for example Global System for Mobile Communications (GSM) systems.

In a conventional GSM mobile cellular telephone system, a mobile station (MS) such as a mobile telephone handset communicates through a radio link with one of a number of fixed base transceiver stations (BTS) distributed at different
10 geographical locations throughout the area of coverage of the system. Clusters of BTS's are connected to a base station controller (BSC) through landlines. Subgroups of the BTS's may be coupled through a hub to the BSC. Groups of BSC's are coupled by means of respective landlines to a mobile switching centre (MSC). The MSC, in addition to being connected to other BSCs, has a connection
15 to a public switched telephone network (PSTN). The system permits communication to be established between two MSs, or between a MS and a conventional telephone connected to the mobile system through the PSTN, or to another network.

Conventionally, the landlines that are used to connect each BTS to its hub,
20 or direct to the BSC, are leased from a terrestrial telecommunications system provider. The leased line needs to have sufficient bandwidth for the peak data traffic flows that occur in use in the network, with the result that during periods of low system utilisation, the bandwidth of the lines is not fully utilised. However, the leased line is rented on a continuous basis rather than on its level of utilisation
25 and so the cost-effectiveness of the lines decreases during periods of low use. A typical so-called E1 (or T1 in the USA) leased digital line offers a bandwidth of 2 MB/s whereas typical data rates between a BTS and its associated hub are of the order of 1 MB/s or less.

Terrestrial system providers also offer digital leased lines, which can be
30 rented with a fixed bandwidth of $N \times 64$ kb/s, where N is an integer typically from 1 - 30. These lower-bandwidth leased lines are suitable for providing the connection between each BTS and the BSC, either via a hub or directly. The leased line connection to a BTS suffers from a disadvantage that in order to

provide sufficient bandwidth when the BTS is operating close to its maximum utilisation level, the bandwidth needs to be selected to be higher than that needed for the traffic levels that occur for most of the time. This increases the cost of the leased line. Similarly, an E1/T1 leased line which can deal with peak levels
5 between the hub and the BSC may provide excessive capacity for average traffic levels that can occur during normal levels of utilisation of the system. Similarly, if the capacity of the BTS is expanded, additional bandwidth may be needed, i.e. another leased line may be required which will be inefficient and costly for average traffic flow, but needed in order to handle peak traffic flow rates.

10 The present invention provides a solution to this problem. In accordance with the invention, there is provided a mobile telephone system comprising a base transceiver station for providing radio communication with one or more mobile stations; a control station for providing call connections between a mobile station and other network terminations; a communication link for providing a first
15 communication path for signals communicated between the base transceiver station and the control station; the base transceiver station and the control station further having connections for communication with a communications network; and control means operable to selectively provide a second communication path, through the communications network, for augmenting the bandwidth available on
20 the first communication path for signals communicated between the base transceiver station and the control station.

Conveniently, the communication link comprises a leased line, so as to provide the first communication path, whereas the communication network is an integrated services digital network (ISDN) so that the second communication path
25 can be selectively set up through the ISDN to provide additional bandwidth for the signals in the event of high system utilisation.

The ISDN is billed to the user according to the amount of time it is used and so the bandwidth available for the signals can be augmented by providing the second communication path, with the cost only being incurred for the time it is
30 used for the second path. In this way, the leased line can be selected to have a bandwidth which can be used at a relatively high utilisation rate during normal operation, because in the event of higher utilisation rates, the second path can be

selectively connected to handle the additional 'peak' bandwidth requirement that occurs during high levels of system use.

In a preferred arrangement, for each call traffic may be carried on either the first path or the second path, but control signalling between the mobile station
5 and the network termination is always carried on the first path.

The invention also includes a method of providing a communication channel for mobile telephony wherein a base transceiver station provides radio communication with a mobile system and the base transceiver provides communication with a control station, the method comprising providing a first
10 communication path with a predetermined bandwidth for signals communicated between the base transceiver station and the control station through a fixed communication link, and selectively providing a second communication path for signals communicated between the base transceiver station and the control station through a communication network for augmenting the available bandwidth for the
15 signals.

When a call is connected through the system, the time required to establish connection may typically be greater through the first path than through the second path, for example where the first path comprises a leased line and the second path consists of an ISDN. Billing to the user is established by a "call-
20 connect" signal which is transmitted back, typically to the BTS in order to signal that the connection has been made and that billing can commence. Discrepancies could arise, either when the call-connect signal over the leased line arrives first, in which case the MS user would be charged for the time between the arrival of the call-connect signal and the actual time of connection over the ISDN. Conversely, if
25 the call connect signal over the ISDN path were to arrive first (or the call-connect signal over the leased line fails to arrive at all, for example because the call is not answered) the mobile network operator will be charged for the ISDN link before the MS user is connected, thereby incurring an unnecessary cost to the mobile network operator. Note that the ISDN call-connect signal only relates to the
30 connection between the BTS and the BSC.

In order to ensure that there are no such billing differences for the ISDN path and the route through the leased line, the invention preferably includes means

for initiating billing for use of the first and second paths in a predetermined time relationship in response to initiation of a call connection.

Preferably, the system has means for transmitting respective call connect signals along the first and second communication paths in response to
5 establishment of respective paths, and means for preventing transmission of the call connect signals until both paths are established and means responsive to reception of the call connect signals for initiating time-related billing for the first and second paths respectively.

Preferably, this may be achieved by arranging that the call connect signals
10 are transmitted along both the first and second communications paths from one end to the other such that they arrive at the other end substantially simultaneously.

In order that the invention may be more fully understood an embodiment thereof will now be described by way of example with reference to the
15 accompanying drawings in which:

Figure 1 is a schematic block diagram of a mobile telephone system in accordance with the invention;

Figure 2 illustrates an alternative configuration in which a BTS is connected directly to the BSC without a hub;

20 Figure 3 illustrates a call connection protocol;

Figure 4 illustrates in more detail signal configurations used to communicate between the BTS and BSC shown in Figure 2; and

Figure 5 is a graph illustrating bandwidth variations that occur with time for data communication between the BTS and BSC shown in Figure 2.

25 Referring to Figure 1, a cellular mobile GSM digital telephone network is shown which includes a plurality of base transceiver stations BTS1, BTS2 distributed at various locations throughout the area of coverage provided by the system. Each BTS1, 2 can communicate by digital cellular GSM techniques with mobile system such as mobile telephone handsets MS1, 2. As shown in Figure 1,
30 BTS1 and BTS2 are connected by means of leased digital landlines 1, 2 to a hub H1 which is connected by landline 3 to a BSC and an associated cross-connect CC1. The BSC is connected by a further line 4 to a mobile switching centre MSC which is connected by lines 5, 6, 7 to further network terminations, both mobile

(via further MSCs, not shown) and fixed (via a conventional public switched telephone network PSTN). A conventional telephone handset 8 is shown connected by line 9 to a digital local exchange DLE which forms part of the PSTN.

Figures 2 and 4 show a simplified network for illustrative purposes, having a single mobile station (MS), and base transceiver site (BTS), the latter connected directly to the base site controller (BSC) (i.e. not via a hub). The BTS and BSC have ISDN telephone connections. The BTS and BSC are both under the control of a Network Management system (NM) which monitors and controls the operation of the cellular network.

Figure 3 is a flow chart showing seven steps S1 to S7 which take place during call set-up. It should be noted that step S3 takes place in parallel with steps S2 and S4.

Figure 5 is a graph of the bandwidth requirement for signal communication between the BTS and BSC as a function of time. The maximum bandwidth that can be handled by path P1 is shown by dotted line 20 and the additional bandwidth that can be provided by path P2 is shown by dotted line 21. Thus, when the graph 22 lies below line 20, path P1 can be used alone but path P2 is required for the shaded areas 23 shown in the graph.

Referring now to Figure 1 in more detail, the leased lines 1, 2, 3 are usually leased from a terrestrial system provider. A conventional full so-called E1 digital leased line offers a bandwidth of 2 MB/s. However, the bandwidth for data from typical BTS is of the order of 1 MB/s and so an E1 leased line would have an inefficient bandwidth utilisation for the connection between each BTS and the associated hub H1. An alternative offered by terrestrial system providers is to lease bandwidth on a $N \times 64$ kb/s basis for which the GSM system provider leases from the terrestrial system provider a bandwidth allocation of $N \times 64$ k/s on a continuous basis, N being a fixed integer selected depending upon the utilisation rate of the BTS. Thus, if the BTS is expected to handle a large number of calls, N will be selected at a relatively high value, whereas if the BTS is located in a position where a lower rate can be expected, N will be selected to have a lower value. Once selected by the system provider, N cannot readily be changed. Renting a line in this way is cheaper than an E1 leased line but the value of N needs to be carefully selected. It is to be understood that the utilisation rate of the

GSM system varies greatly depending on a number of factors such as the time of day, but not all factors can be predicted; for example, users may randomly distribute themselves in the vicinity of one particular BTS at one particular time, thereby raising the utilisation rate. The value of N for the line is thus selected as a compromise between the maximum possible bandwidth required for full capacity of the BTS and the average utilisation rate that usually occurs for the BTS. However, this can lead to inefficient use of the bandwidth of the lines 1, 2, 3 with the disadvantage that the GSM system user has to rent more bandwidth than is normally used, in order to deal with peak demand and thereby provide a satisfactory service to mobile system users.

The present invention provides a solution to this problem. Considering the BTS1, a second signal communication path is provided between BTS1 and the associated hub H1 through an integrated services digital network ISDN 10 (shown in Figure 1 in two portions 10a, 10b). This second communication path includes a first link 11 from the hub H1 to the network 10a and a second link 12 from the network 10a to BTS1. Corresponding links are provided to all of the BTS's connected to the hub. Thus, for BTS2, link 13 together with link 11 provide a corresponding second communication path to augment the first path 2. Thus, in accordance with the invention, the bandwidth for the first communication path P1 provided by leased line 1, can be selected to have a lower value of N than hitherto so that its bandwidth is used more efficiently during normal use. In the event that the number of calls increases so that a higher bandwidth is required between BTS1 and H1, the system is operative to selectively establish a second communication path P2 through the ISDN 10a via links 11, 12 thereby augmenting the available bandwidth. Whilst the leased line is billed on a continuous time basis, use of the ISDN is billed on the time for which it is connected, so that it is only necessary to pay for the ISDN for the period that the second communication path through links 11 and 12 is actually connected. Thus, charges are only incurred whilst a connection is made in respect of the second communication path, so that the second path is only paid for when needed.

Considering now the connection to the BSC, the bandwidth of the various signals received at hub H1 are multiplexed and communicated on a third path through leased line 3 to the BSC and its associated cross connect CC1. The

combined bandwidth of the signals distributed by the hub H1 is somewhat greater than the bandwidth of signals communicated between each individual BTS and the hub so that the use of an E1 leased line for the line 3 is appropriate. However, during periods of heavy use of the system, the bandwidth of the signals may
5 exceed the available bandwidth of the line 3. In order to overcome this problem a fourth communication path may be established through the ISDN 10 through portion 10b, by means of links 14, 15 in a similar way to that described with reference to the BTS's. In this way, a higher level of bandwidth utilisation can be achieved for the line 3, with peak demand being channelled through the ISDN,
10 through links 14, 15 during periods of need, rather than on a continuous basis. Other architectures are possible. For example, the base transceiver sites BTS may be connected directly to the mobile switching centre MSC. The ISDN or similar network may be used to augment the bandwidth over any of the links in these architectures.

15 The signal communication protocols will now be described in more detail with reference to Figure 2, which shows a simplified version of the network with only one BTS connected directly to the BSC, it being understood that the actual network in practice will include many links, as exemplified in Figure 1. In Figure 2, the BTS is connected by a leased line P1 to the BSC and the connection can be
20 established over path P2 through the ISDN. The BTS is given its own ISDN telephone number, in this example, 01999 643997. Similarly, the BSC is given an ISDN telephone number 01111 645444. The BTS can make a connection to the BSC through ISDN by dialling the appropriate telephone number i.e. 01111 645444. The BSC can similarly form a connection to the BTS. Communication
25 through the ISDN is according to signal format LAPD, on the D channel in a manner known per se.

An example of a call connection procedure will now be given, in which the handset MS initiates a connection to the telephone 8, which in this example has the telephone number of 0111 274 6991. Referring to Figure 3, at step S1, the
30 user of the mobile handset MS operates its dial pad to dial the telephone number of telephone 8 (Figure 2) and presses the "send" button in order to initiate the call. Signals are transmitted in GSM format to the BTS and a call connection is established in a conventional manner over the first communication link P1 that

comprises an N x 64 kb/s leased line connected to the BSC, and then through the MSC over line 4, the PSTN over line 7 and thence to the telephone 8 through the DLE and line 9. This is shown at step S2.

Referring to Figure 2, network management NM may determine that the
5 bandwidth of path P1 is insufficient to process the requested call connection and that it is appropriate to open a second communication path P2 through the ISDN. If this is the case, the BTS calls the BSC via the ISDN by transmitting calling signals for telephone number 01111 645444, as shown at step S3 in Figure 3.

There may be a time difference between the time taken to open the path
10 P2 through the ISDN and the call connection through path P1 and paths 4, 7 and 9. In particular, the call connection through path P1 may not be completed if the call is not answered or the called party is engaged on another call. In order to accommodate these different set-up times, the BSC waits for an indication from the MSC that the call connection to telephone 8 has been established, as shown at
15 step S4, after which, at step S5, the BSC transmits call connect signals C1, C2 back to the BTS over the paths P1 and P2 respectively, with timings selected so that C1 and C2 arrive simultaneously at the BTS, as shown at step S6. Thus, the time billing for the call for the ISDN route P2 is the same as that for the conventional landline route P1 and no billing discrepancies thereby occur.

20 The described system also allows telephone 8 to call the mobile station MS, in which case the connection over path P2 is established by the BSC calling the BTS i.e. by dialling telephone number 01999 643997.

Similarly, the invention allows suitable control of call disconnect signals for paths P1 and P2.

25 The call connection scheme is also configured to handle dropped calls (when the MS moves out of the radio coverage area) and handover (when a mobile station moves from one BTS to another).

For security purposes, the BTS and the BSC are configured to check the identity of calling stations via the ISDN using calling line identifying (CLI) signals.
30 If the calling number does not correspond to a known BSC or BTS number, the system may record the calling number so that data can be sent to the network management system NM for review and, if the number occurs regularly, further action can be taken if necessary.

The configuration of the signals transmitted between the MS, BTS and BSC will now be described in more detail with reference to Figure 4. The mobile handset MS when using GSM techniques typically transmits at a data rate 22.8 kb/s with speech coding of 13 kb/s, over a radio link to the BTS. For the leased
5 line P1, 4:1 multiplexing may be used. The line P1 typically has a bandwidth of $N \times 64$ kb/s in which case 4×13 k is multiplexed into 1×64 k time slots. For the path P2, the so-called ISDN2 channel provides 2×64 kb/s channels available for data transceiver which can therefore handle 8 multiplexed calls. The connection
10 between the ISDN 10 and the BSC comprises 30 channels so that up to 15 BTS's can be connected to the BSC each with 2×64 kb/s channels.

Since the path P2 can handle more than one call simultaneously, software is provided to ensure that no channels are in use before the path P2 is disconnected to avoid unwanted call disconnection. Also, a check can be made
15 when a call is initially being set up, whether the path P2 is already open for another call, in order to avoid unnecessarily setting up a further path through the ISDN.

In an alternative configuration, the data is transmitted between the MS and BTS at half rate i.e. with speech at 7 kb/s in which case 8:1 multiplexing can be used for the paths P1, P2.

20 At times of low demand it is undesirable for the system to route calls by way of path P2, because this leaves unused capacity on path P1, which is already paid for as it is a leased line. The bandwidth requirement may be judged on a call-by-call basis in which case the local network management may instruct the BTS/BSC whether the path P2 is needed. However, it is undesirable for the system
25 to select path P1 to carry a call if this would result in very little, or no, capacity remaining to set up further calls. It would be possible to transfer calls from one path to the other whilst in progress, for example if capacity is required for more call set-up signalling on path P1, but to the extra time required to make a signalling channel available on path P1 by transferring a call from path P1 to path P2 would
30 increase call set-up times unacceptably. It is therefore desirable to allocate calls to path P2 such that sufficient capacity always remains on path P1 to handle the signalling required for the level of call traffic expected. The decision to select path

P2 in order to augment the available bandwidth, can be made in a number of different ways.

Firstly, it can be made according to the time of day or some other appropriate period determined by traffic flow trend analysis. As shown in Figure 5, the bandwidth requirement typically varies with time and for some locations, there may be a recognisable diurnal or other pattern, in which case path P2 can be switched on for periods of high use predicted by the BTS/BSC or NM.

Also, local network management at the BTS/BSC level can detect traffic levels rising towards the limit 20, at which time the second path P2 is switched on to augment the available bandwidth.

Whilst the invention has been described in connection with a GSM network, other transceiver techniques can be used, for example in DCS 1800, PCS (DCS 1900), JDC, DAMPS. The invention is also applicable to analogue cellular systems.

CLAIMS

1. A mobile telephone system comprising a base transceiver station (BTS1) for providing radio communication with one or more mobile stations (MS);
5 a control station (BSC) for providing call connections (4,7) between a mobile station (MS) and other network terminations (8);
a communication link (1, 3) for providing a first communication path (P1, P3) for signals communicated between the base transceiver station (BTS) and the control station (BSC);
10 the base transceiver station and the control station further having connections for communication with a communications network (10); and
control means (NM) operable to selectively provide a second communication path (P2), through the communications network, for augmenting the bandwidth available on the first communication path for signals communicated between the
15 base transceiver station (BTS) and the control station (BSC).
2. A system according to claim 1 including means for initiating time billing for the first and corresponding second paths in a predetermined time relationship in response to initiation of a dialled call connection between a mobile station MS and
20 a network termination 8.
3. A system according to claim 2, including means for transmitting which respective call connect signals (C1, C2) along the first and second communication paths (P1, P2) in response to establishment of respective paths, means for
25 preventing transmission of the call connect signals (C1, C2) until both paths are established and means (BTS) responsive to reception of the call connect signals for initiating time-related billing for the first and second paths respectively..
4. A system according to claim 3 including means for transmitting call
30 connect signals (C1, C2) along the first and second communication paths (P1, P2) from one end to the other such that they arrive at the other end substantially simultaneously.

5. A system according to claim 1, 2, 3 or 4 wherein the control means provides the second communication path according to the time of day.
6. A system according to any preceding claim wherein the control means
5 includes network management means for detecting usage of the first path and for selectively operatively connecting the second path in accordance with such usage.
7. A system according to claim 6 wherein the control means is arranged to provide the second path if detected usage of the first path exceeds a given level.
- 10
8. A system according to any preceding claim wherein the control means includes means responsive to a dialled call attempt for determining whether the first path offers sufficient bandwidth for the call, and if not, routing the call through the second path.
- 15
9. A system according to any preceding claim wherein, for each call connected, traffic is carried on either the first path or the second path, according to the operation of the control means (NM) but in either case control signalling between the mobile station (MS) and the network termination (8) is carried on the
20 first path.
10. A system according to any preceding claim wherein the control station comprises a controller (BSC) for controlling said base transceiver station (BTS), the first and second communication paths being provided between the controller (BSC)
25 and the base transceiver station (BTS).
11. A system according to claim 10 including a hub (H1) for controlling a plurality of the base transceiver stations (BTS1, 2), the first and second communication paths (1, 2; 11, 12, 13) being provided between the hub and a
30 base transceiver station.
12. A system according to claim 11 including a plurality of said base transceiver stations connected to the hub, and respective said first and second

communication paths being provided between the hub and each base transceiver stations.

13. A system according to claim 11 or 12 including a third communication
5 path (3) between the hub and the controller (BSC), and means for selectively providing a fourth communication path (14, 15) through the network between the hub and controller (BSC).

14. A method of providing a communication channel for mobile telephony,
10 wherein a base transceiver station provides radio communication with a mobile system and the base transceiver station provides communication with a control station; the method comprising providing a first communication path with a predetermined bandwidth for signals communicated between the base transceiver station and the control station through a fixed communication link, and selectively
15 providing a second communication path for signals communicated between the base transceiver station and the control station, through a communication network for augmenting the available bandwidth for the signals.


15. A method according to claim 14 including initiating time billing for the first
20 and second paths in a predetermined time relationship in response to initiation of a dialled call connection.

16. A method according to claim 15, in which respective call connect signals are transmitted along the first and second communication paths in response to
25 establishment of the respective connections, and in which transmission of one or both of the call connect signals is prevented unless both connections are established.


17. A method according to claim 16 wherein call connect signals are
30 transmitted along the first and second communication paths from one end to the other such that they arrive at the other end substantially simultaneously, and time billing is initiated for the first and second paths respectively in response to reception of the call connect signals.

18. A method according to claim 14, 15, 16 or 17 wherein the second communication path is provided according to the time of day.
- 5 19. A method according to claim 14, 15, 16, 17 or 18 wherein the second path is selectively operatively connected in accordance with the degree of usage of the first path.
20. A method according to claim 17 wherein the second path is provided if
10 detected usage of the first path exceeds a given level.
21. A method according to claim 14, 15, 16, 17, 18, 19 or 20 wherein the call is routed through the second path in response to a call attempt if the first path does not offer sufficient bandwidth for the call.
- 15 22. A method according to any of claims 14 to 21 wherein for each call, traffic is carried on either the first path or the second path, but in either case control signalling between the mobile station (MS) and the network termination (8) is carried on the first path.
- 20 23. A method according to any of claims 14 to 22, the first and second communication paths being provided between a controller (BSC) and a base transceiver station (BTS) controlled by said controller (BSC).
- 25 24. A method according to claim 23 wherein first and second communication paths (1, 2, 11, 12, 13) are provided between a hub (H1) and one or more base transceiver stations (BTS1, 2) controlled by the hub (H1).
- 30 25. A method according to claim 24 wherein a fourth communication path (14, 15) is selectively provided through the network between the hub and controller (BSC) to augment a third communication path (3) existing between the hub and the controller (BSC).

26. A mobile telephone system substantially as described with reference to the drawings.
27. A method of providing a communication channel for mobile telephony,
5 substantially as described with reference to the drawings.




2/4



3 / 4

Fig.3.



4/4

Fig.4.





Fig.5.



INTERNATIONAL SEARCH REPORT

International Application No
PCT/GB 96/01711

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 H04Q11/04 H04Q7/00 H04Q3/66 H04Q7/24

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	EP,A,0 462 728 (NORTHERN TELECOM LTD) 27 December 1991 see column 3, line 15 - column 4, line 6; figures 2A,B ---	1,5-14, 18-27
Y	TELECOMMUNICATION ACCESS NETWORKS. TECHNOLOGY AND SERVICE TRENDS. PROCEEDINGS OF THE IX INTERNATIONAL SYMPOSIUM ON SUBSCRIBER LOOPS AND SERVICES - ISSLS 91, AMSTERDAM, NETHERLANDS, 22-26 APRIL 1991, ISBN 0-444-89050-5, 1991, AMSTERDAM, NETHERLANDS, NORTH-HOLLAND, NETHERLANDS, pages 69-75, XP000516574 FINEBERG V ET AL: "Wireless impact on personal telecommunications services" see the whole document --- -/--	1,5-14, 18-27

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- *Z* document member of the same patent family

Date of the actual completion of the international search

6 December 1996

Date of mailing of the international search report

17.12.96

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 1
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Janyszek, J-M

INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 96/01711

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	EP,A,0 398 183 (NORTHERN TELECOM LTD) 22 November 1990 see the whole document ---	1,6-14, 19-27
Y	FUJITSU SCIENTIFIC AND TECHNICAL JOURNAL, SUMMER 1992, JAPAN, vol. 28, no. 2, ISSN 0016-2523, pages 181-191, XP000312059 HAYASHI T ET AL: "Corporate information network system: COINS" see paragraph 3 - paragraph 4.5; figures 2-6 ---	1,5, 10-14, 18,24-27
Y	GLOBECOM '89. IEEE GLOBAL TELECOMMUNICATIONS CONFERENCE AND EXHIBITION. COMMUNICATIONS TECHNOLOGY FOR THE 1990S AND BEYOND (CAT. NO.89CH2682-3), DALLAS, TX, USA, 27-30 NOV. 1989, 1989, NEW YORK, NY, USA, IEEE, USA, pages 539-542 vol.1, XP000091154 EBERL L H ET AL: "Integrated ISDN D-server for intelligent networking" see the whole document ---	1,6-14, 19-27
Y	PATENT ABSTRACTS OF JAPAN vol. 018, no. 428 (E-1591), 10 August 1994 & JP,A,06 132969 (NEC CORP), 13 May 1994, see abstract -----	1,6,7, 14,19,20

INTERNATIONAL SEARCH REPORT

International Application No
PCT/GB 90/01711

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP-A-0462728	27-12-91	GB-A- 2245455	02-01-92
		CA-A- 2044435	19-12-91
		NO-B- 179388	17-06-96
		US-A- 5260987	09-11-93

EP-A-0398183	22-11-90	US-A- 4924500	08-05-90
		AU-B- 620240	13-02-92
		AU-A- 5379390	22-11-90
		CA-A- 1312394	05-01-93
		CN-B- 1022788	17-11-93
		DE-D- 69024257	01-02-96
		DE-T- 69024257	10-10-96
		JP-A- 2311065	26-12-90
JP-B- 7077402	16-08-95		

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.